



| | |
|-------------------------|--|
| Single line pull | 6000lb |
| Motor | 12V DC permanent magnet |
| Gear train | SEALED 3 Stage Planetary metal gearing |
| Gear Ratio | 136 : 1 |
| Clutch | Cam activated |
| Braking Action | Mechanical & Dynamic |
| Drum size | Diameter 2.0" / Length 2.9" |
| Weight | 28 |
| Dimensions | 14 ½ x 4 ½ x 4 ¾ |
| Cable | 65 ft of 1/4" Amsteel Blue cable |
| Battery | 12 Amp/hour minimum |
| Mount Pattern | 3" x 6.67" |


linepull

| Layer of Cable | Rated Line Pull Per |
|----------------|---------------------|
| | Lbs |
| 1 | 6000 |
| 2 | |
| 3 | |
| 4 | |


linespeed – ampdraw

| 6,000 lbs Line Speed & Amp Draw (1st Layer) | | | | | | | | | | | |
|---|---------------|---------|-----|------|------|------|------|------|------|------|------|
| Pull | Lbs | No Load | 500 | 1000 | 1500 | 2000 | 3000 | 3500 | 4000 | 5000 | 6000 |
| Line Speed | ft/min | 26 | 20 | 16 | 14 | 11 | 7 | 6 | 4 | 2 | 2 |
| Current | amps | 31 | 50 | 86 | 121 | 155 | 225 | 248 | 288 | 330 | 330 |